


Customization & Professionalization




PANDPCO TRADING LIMITED


 342 Tennyson Drive
Oakville Ontario
Postcode: L6L 3Y9
Canada


 sales@pandpco.ca
info@pandpco.ca
guomail188@gmail.com


 www.pandpco.ca


 +1 (647)-7296873


 +1 (647)-7296873


 +1 (416)-4093186

 972767760

 PANDPCO188

 +1 (416)-4093186

 +1 (416)-4093186



15,00BPH (oil bottle)
Rotary Hot Melt Glue Labeling Machine



Product performance characteristics

1. This model is suitable for oval bottle OPP film, pearl film and other ring around the edge.
 2. Suitable for mineral water, beverage and other industries of plastic bottles of hot melt adhesive labeling machine.
 3. Japan Sanyo imported servo motor and Siemens PLC control, simple operation, stable and reliable operation.
 4. The use of advanced glue system and vacuum drum combination to ensure high precision labeling. Only in the label at both ends of the glue, reduce the amount of glue used to save costs.
 5. Synchronous pulley drive system, and the use of screw and star wheel with the inlet and outlet bottles to ensure high-speed operation, the product out of smooth and stable.
 6. Production speed of up to 3000 bottles / hour, can be connected with the filling line production, greatly improving the production speed, saving production costs.
- Labeling process: into the bottle → positioning → detection → cut → standard → glue → glue → labeling → raise the standard → a bottle.



Technical Data

Model No. PYJ-ULPL-1615R	Specification	Remarks
Design Rated capacity	15,000 bottles / hour	production speed can be adjusted according to the actual situation
Labeling station number:	16	Every circle
Maximum speed of the label	150 m / min	
Maximum labeling speed	60 m / min	production speed can be adjusted according to the actual situation
Labeling Product Type	Square Bottle	suitable for plastic, metal, glass and other square containers on the label
Labeling bottle Type	Full Bottle	
Labeling Mold	Circle Label	
Delivery accuracy	± 1mm	
Labeling accuracy	± 1mm	
Label maximum width (height)	150mm	standard width, according to the actual product size to increase the width
The maximum length of the label	500mm	
The maximum diameter of the label	600mm	
Conveyor belt height	1100 ± 1mm	
Transmission line speed	30 m / min	
The core diameter	152mm	
Speed adjustment mode		stepless speed regulation
Labeling colloid hot melt adhesive		only in the label two sizing
Label type		OPP film label, paper and plastic composite film label, paper label
Product Size		Customers offer bottles
The glue temperature	40 ~ 100 degree centigrade	
Power supply	three - phase 380V 50Hz	
Power	8000W	Control: 220V/AC/24DV
Labeling machine host size	2990 × 2400 x 2400mm	
Machine weight	3000Kg	
Labeling the number of molds	the standard configuration for a set	to meet the provision of a specification products shall prevail, each set of mold, including into the bottle screw, into the bottle star wheel, a bottle star wheel, positioning bottle care, etc.