

Customization & Professionalization



24,00BPH (330ml bottle)
Rotary Hot Melt Glue Labeling Machine



PANDPCO TRADING LIMITED

 342 Tennyson Drive
Oakville Ontario
Postcode: L6L 3Y9
Canada

 sales@pandpco.ca
info@pandpco.ca
guomail188@gmail.com

 www.pandpco.ca

 +1 (647)-7296873

 +1 (647)-7296873

 +1 (416)-4093186

 972767760

 PANDPCO188

 +1 (416)-4093186

 +1 (416)-4093186






Product performance characteristics

1. User-friendly touch screen, simple and intuitive operation, full-featured, with a wealth of online help function;
2. The bidder system adopts German high speed servo motor and controller, which ensures the accuracy and stability of high speed bid transfer and cutting standard.
3. The main motor with high power imported motor, to ensure the stability of the machine running and handling;
4. German label color detection electric eye, improve the accuracy of the standard;
5. Perfect operation of the protection system can be achieved such as missing standard, leakage paste, lack of bottles, card bottles, temperature detection, air pressure and other downtime alarm;
6. Due to the use of rotary mold positioning labeling, to ensure the labeling of the sealing accuracy and stability;
7. The use of Siemens and other world brands imported electrical components to ensure that the machine's long-term stability and reliability;
8. Equipment to set up online interface function, easy to line with other equipment production

Labeling process: into the bottle → positioning → detection → cut → standard → glue → glue → labeling → raise the standard → a bottle.



Technical Data

Model No. PYJ-ULPL-2024R	Specification	Remarks
Design Rated capacity	24,000 bottles / hour	production speed can be adjusted according to the actual situation
Labeling station number:	20	Every circle
Maximum speed of the label	150 m / min	
Maximum labeling speed	60 m / min	production speed can be adjusted according to the actual situation
Labeling Product Type		suitable for plastic, metal, glass and other square containers on the label
Labeling bottle Type	Full Bottle	
Labeling Mold	Circle Label	
Delivery accuracy	± 1mm	
Labeling accuracy	± 1mm	
Label maximum width (height)	150mm	standard width, according to the actual product size to increase the width
The maximum length of the label	500mm	
The maximum diameter of the label	600mm	
Conveyor belt height	1100 ± 1mm	
Transmission line speed	30 m / min	
The core diameter	152mm	
Speed adjustment mode		stepless speed regulation
Labeling colloid hot melt adhesive		only in the label two sizing
Label type		OPP film label, paper and plastic composite film label, paper label
Container diameter	40mm-100mm	
The glue temperature	120 ~ 160 degree centigrad	
Power supply	three - phase 380V 50Hz	
Power	8000W	Control: 220V/AC/24DV
Labeling machine host size	2990 × 2500 x 2000mm	can be adjusted according to customer requirements
Machine weight	3000Kg	
Labeling the number of molds	the standard configuration for a set	to meet the provision of a specification products shall prevail, each set of mold, including into the bottle screw, into the bottle star wheel, a bottle star wheel

